

DECLARATION OF PERFORMANCE FIBO-TRESPO/RESPATEXNr. **001/FT-CPR-2013/rev. 2**

1. Unique identification code of product category: Processed plywood for interior use in wet areas.
2. Tracking: production number applied pr. panel/unit.
3. Application: Respatex is a 7-layer X-veneer glued with high pressure laminate on both sides with a thickness of 10,2 mm and a density approx. 800 kg/m³ with locking system for use in vertical stud partitions in wet areas. The panel is **CE** - marked and meet the requirements for not carrying plywood for interior use in humid conditions according to EN 636-2. Product use and conditions of use described in the NBI Technical Approval No. 2289, SITAC type approval certificate No. 0409/02, VTT-C-2753 08 and MK 7.32/1462.
4. Name, registered trademark: Fibo-Trespo/Respatex.
5. Manufacturer: Fibo Trespo AS, Industriveien 2, 4580 Lyngdal, Norway
6. Systems for the assessment and control of construction works constant performance: System 2 +
7. Performance declaration applies wood-based panel, manufactured and labeled in accordance with the approved European Construction Products Regulation (305/2011/EEC) and the requirements of Annex ZA1 of the harmonized standard: EN 13986:2004, with production certificate No. 1049 from Sintef Building and Infrastructure (1071).
8. Relevant performance in the application:

Property	Value	Test method
Water resistance	< 1,5 bar/week	EN 14891 annex A7
Water vapor resistance	14 m	EN 12572
Fire class	D - s1, d0	EN 13501-1
Formaldehyde class	E 1	EN 717-1
Screw extension	1740 N	EN 320

9. The performance of this product, as specified in section 1 and 2, is in accordance with the requirements of EN 636:2012 and additional properties specified in the table in section 8.

The performance statement is issued on the sole responsibility of the manufacturer, as defined in Section 5.

Signed for and on behalf of the manufacturer:

Lyngdal, 12.11.2014

(place and date of publication)



Arvid Thompsen
Product manager